





Reliable Economical – Fits Your Need Reusable 3D Accelerometer Sensor Data Download Available

Easy Setup To Reduce Residual Paralysis Complete NMBA Monitoring for OT & ICU Nerve Mapper cum Locator





Specifications:

Pulse Amplitude (mA)

Pulse Width (m sec)

Load Impedance (kΩ)

Stimulating Mode

Frequency (Hz)

Compact & User friendly Color LCD Display Hand held or Pole Mounted Displays Set and Delivered Current Monophasic Constant Current Stimulator Battery Operated - 4 * 1.5V AA (LR6)Duracell

0.0 to 80.0 mA

TW, TOF, DB, PTC, TET,

I_{Supra max} & Auto

0.2ms

1, 2 & 5Hz

5 K O

TOF Graph



TOF + Trend Graph



• Specifications and design subject to change without notice



Manufactured By: Medilogix Medical Technologies Pvt Ltd L 2 F, 2nd Floor, Sarvamangala Colony, 42nd Street, 6th Avenue, Ashok Nagar, Chennai - 600 083. Ph: 044 2471 7220, 93452 65450, Email: contact@medilogix.in www.medilogix.in



0.2 to 5 mA

0.3,0.5, 1.0ms

0.05.0.1.

1, 2, 3Hz

5 K O

Locate

Marketed By:

Delvin Formulations Pvt. Ltd. A Division of Saimirra Innopharm Pvt. Ltd., Plot No.79, Abhirami Towers, 1st Floor, Masilamani Nagar, 2nd Street, Kanniamman Koil Main Road, Vanagaram, Chennai - 600 095.

For Enquiries - () 9345265450

0.0 to 20 mA

0.3,0.5, 1.0ms

0.05, 0.1,

1, 2, 3Hz

12 KO

Map