





Reliable Economical – Fits Your Need Reusable 3D Accelerometer Sensor Data Download Available

Easy Setup To Reduce Residual Paralysis Complete NMBA Monitoring for OT & ICU





Specifications:

Compact & User friendly Color LCD Display Hand held or Pole Mounted Displays Set and Delivered Current Monophasic Constant Current Stimulator Battery Operated - 4 * 1.5V AA (LR6)Duracell



| | NMT |
|----------------------|--|
| Pulse Amplitude (mA) | 0.0 to 80.0 mA |
| Pulse Width (m sec) | 0.2ms |
| Frequency (Hz) | 1, 2 & 5Hz |
| Load Impedance (kΩ) | 5 ΚΩ |
| Stimulating Mode | TW, TOF, DB, PTC, TET, I _{Supra max} & Auto |

• Specifications and design subject to change without notice

TOF + Trend Graph





Manufactured By: Medilogix Medical Technologies Pvt Ltd L 2 F, 2nd Floor, Sarvamangala Colony, 42nd Street, 6th Avenue, Ashok Nagar, Chennai - 600 083. Ph: 044 2471 7220, 93452 65450, Email: contact@medilogix.in www.medilogix.in



Marketed By:

Delvin Formulations Pvt. Ltd. A Division of Saimirra Innopharm Pvt. Ltd., Plot No.79, Abhirami Towers, 1st Floor, Masilamani Nagar, 2nd Street, Kanniamman Koil Main Road, Vanagaram, Chennai - 600 095.

For Enquiries - (2) 9345265450